

Petra SAE 5W-30 Syn-X Motor Oil

PN 1530 (32oz) Specification Sheet



Product Description:

PetraSyn-X Synthetic 5W-30 engine oil is formulated to help improve fuel economy and provide excellent all weather engine protection.

Advantages & Uses:

Petra Syn-X Synthetic 5W-30 engine oil meets or exceeds all automobile and light duty truck warranty requirements for gasoline and turbocharged engines where an API SN/CF SAE 5W-30 engine oil is recommended. Petra engine oil SAE 5W-30 meets or exceeds all requirements for ILSAC GF-5. Petra engine oil contains select viscosity index improvers to provide easier cold weather starting and better high temperature protection demanded by modern high output engines. Follow manufacturer's recommendations for viscosity grade and API service category. This oil is suitable for use and meet or exceed the performance requirements of many automobile manufacturers for service fill oil: 5W-30 (GM 6094M, Chrysler MS 6395Q, Ford WSS-M2C929-A), ACEA A3/B4-04 (including ACEA 2007 version), VW 502 00/505 00, VW 503 01, Mercedes Benz MB p229.5, Porsche and BMW LL-01 (Longlife – 01).

Features:

- Meets or exceeds all automobile and light duty truck warranty requirements for gasoline and turbocharged engines where an API SN and prior categories SAE 5W-30 engine oil is recommended.
- Petra engine oil SAE 5W-30 is energy conserving and meets ILSAC GF-5 specifications.
- Petra engine oil is formulated to help improve fuel economy and provide excellent all weather engine protection.
- Petra engine oil contains select viscosity index improvers to provide easier cold weather starting and better high temperature protection demanded by modern high output engines.

